

Technical Data Sheet

Name: IFC-2937

Revision Date: 2023-08-04

Version:1.3

Product Description

IFC-2937 is applied for modified asphalt, as a modifier of emulsified asphalt. It has good compatibility with both cationic and anionic emulsified asphalt, which greatly improves the softening point and anti-flow characteristics of asphalt, and improves the alkali resistance of asphalt. The mixing of the two materials combines the waterproofing properties of asphalt and acrylate film-forming properties, the viscoelasticity of polymers and weatherability. It is a one-component polymer for waterproof coatings.

Properties

1. Excellent compatibility with anionic and cationic asphalt
2. Excellent low temperature performance
3. Good adhesion

Characteristic data*

Property	Value	Unit
Appearance	Milky white liquid	
Solid content	50±1	%
PH	6-7	
Viscosity	500-800	mPa.s
Tg	-20	°C

*These properties are typical but do not constitute specifications.

Application

IFC-2937 is a kind of polymer asphalt waterproofing emulsion. Please use non-ionic bonded polyurethane thickener when it is compatible with cationic asphalt, and use anionic bonded thickener when it is compatible with anionic asphalt.

Disclaimer

Foshan Shunde Infinechem Co., Ltd. recommends that customers should check with Materials Safety Data Sheet (MSDS) for details about safety instructions. We also suggest that you contact the suppliers of other materials used in our recommended formulations and consult appropriate health and safety regulations prior to use. The

IFC-2937



information contained herein is believed to be reliable. However, nothing in this technical sheet should be considered as a representation of warranty, express or implicit, regarding the product characteristics, application, quality, safety, merchantability or fitness for a particular purpose. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.