

IFC-1304

Elastic emulsion



Technical Data Sheet

Name: IFC-1304

Revision Date: 2023-04-21

Version:1.3

Product Description

IFC-1304 is a new type of self-crosslinking acrylic emulsion developed for elastic emulsion paints.

Properties

1. Excellent colour development
2. Good adhesion and high strength
3. Excellent stain resistance
4. Excellent elongation

Characteristic data*

Property	Value	Unit
Appearance	Milky white liquid	
Solid content	50±1	%
PH(25°C)	7.0-9.0	
Viscosity	800-2500	cps(23°C ,3#,30r/m)
Tg	-18	°C
MFFT	0	°C
Calcium ion stability	Passed	

*These properties are typical but do not constitute specifications.

Storage

The product should be stored in dry condition between 5-35°C with the integrity of the packaging, and prevented from direct sunlight. The validity of this product is for 6 months, performance assessment is recommended before use after shelf life. The product should be protected from freezing during storage. It is suggested to filter before application and use up once the package is open.

Disclaimer

Foshan Shunde Infinechem Co., Ltd. recommends that customers should check with Materials Safety Data Sheet (MSDS) for details about safety instructions. We also suggest that you contact the suppliers of other materials used in our recommended

IFC-1304



formulations and consult appropriate health and safety regulations prior to use. The information contained herein is believed to be reliable. However, nothing in this technical sheet should be considered as a representation of warranty, express or implicit, regarding the product characteristics, application, quality, safety, merchantability or fitness for a particular purpose. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.